

Capacity & Dimensions

24-hour Capacity	up to 650 lb (295 kg)	
Width	40"	102 cm
Height	48"	123 cm
Depth	30"	76 cm
Weight	670 lbs	303 kg

Utility Usage

Water Consumption	about 20-40 gallons (75-150 l.) / day	
Power Consumption	about 75-150 kilowatt hours / month	
Effluent Discharge	about 40-80 gal (150-300 l.) / day	

Utility Connections

- Incoming Water, Power, Data
- Effluent (to sewer line) - 2" OD, 1.5" NPT ID

Utility Requirements (by customer): Inlet Water - 90-110 degree F, 50-80 psi / Discharge - gravity flow or pump (optional) / Ethernet cable for Data Access (our Blue Cloud) / Power - 115 VC, 50 Hz or 110 VAC, 60 Hz



- Space-saving compact footprint
- Designed for low volume food waste generators
- Can process up to **650 lbs (295 kg)** of food waste per day
- Comes equipped with our BioHiTech cloud-based technology to reduce food waste generation



Reduce Food Waste with Data Analytics

Accurate real-time information eliminates the uncertainty about where food waste occurs, how much is being wasted and its associated value. Our Blue Cloud waste tracking technologies forecasts accurate supply chain and inventory needs, standardizes best practices for production, improves future planning for the prevention of waste, and tracks your carbon footprint and credits.



Front

Side

Rear

Top

